

C12RSH2 12" Sliding Dual Compound Miter Saw with Laser Marker

Includes:

- 12 inch 60T TCT Saw Blade (726100)
- Dust Bag (322955)
- Vice Assembly (339624)
- 17mm Box Wrench (333732)

Features:

- **Covered by Hitachi's professional 5-year warranty**
- **Compact slide system** allows the saw head to slide along fixed rails, eliminating the need for rear clearance
- **Laser marker system from Hitachi** increases cutting accuracy
- **Powerful 15 Amp motor** to tackle tough cutting jobs with ease
- **Large sliding fences raise fence height to 5-1/8 inches** to cut up to 7-1/2" crown molding vertically
- **0-57 degree miter angle to the right and 0-45 degree to the left** for flexibility
- **0-45 degree bevel angle range to the right and left** allowing users to quickly and easily flip the saw blade and leave the material in place
- **Positive stops and indications on the miter and bevel scale**, for easy to read measurements and quick settings
- **Carbon brush access**, allows the user to replace the brush as needed to greatly prolong tool life
- **Vertical handle with soft, vibration reducing elastomer grip** adds comfort and control
- **TOOL CARD:** [C12RSH2 Tool Card](#)

Includes:

- 12 inch 60T TCT Saw Blade (726100)
- Dust Bag (322955)
- Vice Assembly (339624)
- 17mm Box Wrench (333732)

Specifications

Compound Cutting Range	Miter: 0-45 Degree L/ 0-31 Degree R Bevel: 0-45 Degree L Miter: 0-31 Degree L/ 0-45 Degree R Bevel: 0-45 Degree R
Amps	15
No-Load Speed	4,000 RPM
Blade Diameter	12"
Miter Cutting Range	0-45 Degree L; 0-57 Degree R
Bevel Cutting Range	Left & Right 0-45 Degree

Positive Miter Stops	L/R 0, 15, 22.5, 31.6, 45 Degrees
Laser Marker	Yes
Saw Blade Drive System	Poly V Belt & Gear
Splinter Guard	Provided (Fixed)
Tool Dimension WxDxH	25-1/2"x36-5/8"x27-15/16"
Tool Weight	59 lbs
Max Cutting Capacities (HxW):	
90 Degree Cross Cut	4-3/16"x12-1/4" or 4-11/16"x10-3/16"
45 Degree Miter (L/R)	4-3/16"x8-5/8" or 4-11/16"x7-1/16"
45 Degree Bevel (L)	2-3/4"x12-1/4" or 2-15/16"x10-3/16"
Compound Cut 45x45 (L/L)	2-3/4"x8-5/8" or 2-15/16"x7-1/16"
Warranty	5-Year
