

UB18DJL 18V Lithium Ion LED Torch/Flash Light (Tool Body Only)

Includes:

- 18V Li-Ion Slide-Type Battery 3.0Ah (BSL1830) (330067)
- 18V Li-Ion Slide-Type Battery 31.5Ah (BSL1815X) (330139)
- 14.4V-18V Li-Ion Rapid Charger (UC18YRSL)

Features:

- Covered by Hitachi's 5-year warranty
- Compatible with Hitachi's 14.4V 18V Lithium Ion slide-type batteries for fade free power, less weight and 3x the total battery life of traditional batteries (batteries and chargers sold separately)
- 247 degree adjustable head on the left-right joint that can maneuver into 7 different positions
- 180 degree adjustable head on the up-down joint that can maneuver into 5 different positions
- Four brightness settings for ultimate convenience and flexibility
- Long 26 hour run time on torch light mode (assuming 18V 3.0Ah battery) for efficient use on a charge
- Delivers 10 to 31 hours of run time (depending on the setting) on flashlight mode (assuming 18V 3.0Ah battery) for maximum lighting needs on a charge
- Hook allows for easy hanging from bars or beams on the jobsite to get light where needed

27 Lux

- Convenient free standing design from floor as needed
- Lightweight at only 0.7 lbs (without battery) for easy transport and storage
- Download the <u>UB18DJL Tool Card</u>

Optional:

- 18V Li-Ion Slide-Type Battery 3.0Ah (BSL1830) (330067)
- 18V Li-Ion Slide-Type Battery 31.5Ah (BSL1815X) (330139)
- 14.4V-18V Li-Ion Rapid Charger (UC18YRSL)

Specifications	
----------------	--

Work Light-Low

Volts	18
Torch Light	6,000 Lux
Work Light- High	110 Lux
Work Light- Mid	55 Lux

Ratteries Included 0

Datulius muluutu

v

Torch Light Run Time (3.0Ah) 26 Hours

Work Light Run Time(3.0Ah) High(10hr), Mid(18hr), Low(31hr)

Torch Light Source LED (3W) x 1

Work Light Source(High) LED (0.5W) x 12

Work Light Source(Med) LED (0.5W) x 6

Work Light Source(Low) LED (0.5W) x 3

Left-Right Joint 7-Position, 270 Degrees

Up/Down Joint 5-Position, 180 Degrees

Warranty 5-Year