

UA3810AB 10-Gallon ASME Certified Reserve Air Tank

Includes:

- (4) 1/4" Quick Connect Couplers with 3/8" NPT (889021)
- (1) 1/4" Quick Connect Coupler [located on Regulator] with 1/4" NPT (888020)
- (1) Safety Relief Valve (889014)
- (1) Industrial Tank Pressure Gauge (889015)
- (1) Industrial Regulated Pressure Gauge (889016)
- (1) Industrial Ball (Shut-Off) Valve on Input (889019)
- (1) 1/4" Industrial Plug (889018)

Features:

- **All fittings included and installed** (except for four end fittings that need to be attached upon removal from packaging, for convenience and value)
- **Certified by the American Society of Mechanical Engineers (ASME)** to ensure compliance with laws and regulations across all U.S. States
- **Industrial ball (shut-off) valve on input** allows the tank to be filled and disconnected from the compressor without draining itself
- **Five quick connect couplers (4 unregulated + 1 regulated)** allow for easy one handed connections of hoses and/or splitters
- **Roll cage design** protects regulator and gauges
- **Industrial pressure gauges** are encased in steel for high durability
- **Angled steel legs** provide additional support, stability, and increase durability despite the abuse endured by hostile jobsite use
- **Steel tubular handle** for easy jobsite transport and added comfort
- **10-gallon capacity** ensures sufficient pressure to power five or more nailers at the same time
- **Reserve air tank connects between the compressor and attached nailers** to bridge the distance of over 200 feet or more, while ensuring PSI remains constant
- **Standard factory installed large knob regulator** is convenient in the event that a nailer (like a palm nailer for instance) might require less PSI than other nailers on the jobsite
- **Professional 1-Year Warranty** for peace of mind
- Available in the USA only
- Download the [UA3810AB Tool Card](#)

Includes:

- (4) 1/4" Quick Connect Couplers with 3/8" NPT (889021)
- (1) 1/4" Quick Connect Coupler [located on Regulator] with 1/4" NPT (888020)
- (1) Safety Relief Valve (889014)
- (1) Industrial Tank Pressure Gauge (889015)
- (1) Industrial Regulated Pressure Gauge (889016)
- (1) Industrial Ball (Shut-Off) Valve on Input (889019)
- (1) 1/4" Industrial Plug (889018)

Specifications

Tank Type	Horizontal Barrel
Tank Capacity	10-Gallon (ASME)
No. of Outputs	Five (4 Unregulated + 1 Regulated)

Tank Pressure Gauge	Yes- Installed
Regulated Pressure Gauge	Yes- Installed
Coupling Sockets	1/4" Industrial x 5
Max Allowed Working Pressure	175 PSI
Input Shut-Off Valve	Yes- Installed
Safety Release Valve	Yes- Installed
Weight	40 lbs
Warranty	1-Year
