

DH40MR 1-9/16" AHB Aluminum Housing Body SDS Max Shank Rotary Hammer- DISCONTINUED

### Includes:

- Depth gauge
- Side Handle
- Injection molded carrying case
- Hex Bar Wrench
- Grease Packs

### Features:

- Click to view [Hitachi 2018 Catalog for Commercial Products](#)
- Click to view the [Dust Collection Attachment 115452](#)
- Click to view the [Dust Collection Attachment 115453](#)
- Fast drilling speed with lower vibration and noise level
- 7.4 ft-lbs of impact energy, delivering high-speed drilling and forcible chipping
- 9.2 Amp motor, increases productivity
- 2-modes of operation, hammer only and hammer & drill for flexibility within a range of applications
- Built-in electronic control circuit, keeps speed constant even as load varies
- Needle-pin slip clutch, for higher slip torque accuracy and safety
- Variable lock system, makes bit replacement simple and offers 12-angle positions for chiseling
- Soft, non-slip Elastomer grip handle, absorbs vibration and improves comfort and handling
- Revolutionary IDI (Internal Double Insulation) technology, incorporated into the housing of the tool greatly improves reliability and extends the tool life
- Removable side handle with depth gauge, improves control and ensures accurate drilling depth
- Download the [DH40MR Tool Card](#)

#### Includes

- Depth gauge
- Side Handle
- Injection molded carrying case
- Hex Bar Wrench
- Grease Packs

#### Specifications

<b>Shank</b>	<b>SDS Max</b>
<b>Chuck Size</b>	<b>1-9/16"</b>
<b>No-Load Speed</b>	<b>240-480rpm</b>
<b>Impact Rate</b>	<b>1320-2650bpm</b>
<b>Impact Energy</b>	<b>7.4 ft-lbs</b>

Impact Energy	1.4 ft/lbs
Amps	9.2
Capacity: Drill Bit	1-9/16"
Capacity: Core Bit	4-1/8"
Modes of Operation	Hammer/Hammer & Drill
Switch	EVS
Handle Type	D
Full Load Vibration	117db
No-Load Noise Level	79.5db
Power Input	950W
Tool Length	17-1/8"
Tool Weight	14.3lbs

---