

W6V4SD2 SuperDrive Collated Screw System

Includes:

• #2 Phillips Bit (Installed)

Features:

- Watch the video demo
- Ideal for drywall to wood and drywall to metal installations
- Features a no-load speed of 0-4,500 RPM and a max torque of 81.5 in-lbs, ideal for faster fastening applications
- Tool-free depth of drive adjustment requires only a press of a block and a turn of the knurled wheel to increase or decrease the depth of the screw
- Tool-free screw length adjustment automatically adjusts as the screw lengths change from 3/4" up to 2-3/16" in length for fast and seamless transitions on the job
- While other tools require multiple attachments for different length screws, the SuperDrive system is ready for work given it **fastens from 3/4" to 2-3/16"** screws with diameters from #6-#12
- Powerful 6.6 Amp motor (750 Watts of input power)
- Body of the screwdriver is covered in a soft, yet durable elastomer compound, which provides a comfortable and slip-resistant grip
- Belt hook incorporated into the body of the screwdriver adds convenience
- Large trigger with lock-on for continuous use is designed for comfort and control during operation
- Gear case and inner cover are constructed out of aluminum to add durability and increase tool life
- Plastic cover keeps the gear case from being scratched or damaged during extreme use
- 24.6 ft power cord is unusually long to allow movement without the hassle of relocating to different power outlets
- Download the <u>W6V4SD2 Tool Card</u>

Includes:

• #2 Phillips Bit (Installed)

Specifications

Power Input 750 Watts Screw Capacity 3/4" - 2-3/16" Screw Diameter #6-#12

No-Load Speed 0-4,500 RPM

Cord Length 24.6 Feet
Bit Shank 1/4" Hex
Max Torque 81.5 in-lbs
Amps 6.6
Weight 5.5 lbs
Warranty 1-Year

