

DH38YE2 1-1/2" Spline Shank Rotary Hammer

Includes:

- Side Handle (330209)
- Dust Cover (993245)
- Depth Stopper (971786)
- Case (331965)

Features:

- Click to view [Hitachi 2018 Catalog for Commercial Products](#)
- Click to view the [Dust Collection Attachment 115452](#)
- Click to view the [Dust Collection Attachment 115453](#)
- **Features** more power, lighter weight, less vibration and lower noise than its well known predecessor
- **Powerful 8.4 Amp motor** delivers 950 watts of input power for maximum productivity
- **Produces 5.9 ft/lbs of impact energy** for faster drilling and chiseling through concrete
- **Two modes of operation** - hammer only and hammer drilling controlled by the simple turn of a knob
- **Low vibration** levels of only 18.8m/s² (full load) for more comfortable operation in hand
- **Low noise** levels of only 95.2 dB (full load) for a less noisy work environment
- **Safety clutch** shuts down rotation in the event of a bound bit for improved user protection
- **Dust resistant cover** protects the tool from dust and debris and prolongs tool life
- **Auto-stop carbon brushes** prevent motor damage and are accessible for simple maintenance checks
- **Sealed grease system** adds to the tools maintenance free operation
- **Soft elastomer handle** provides a secure grip and absorbs vibration for comfort and control during operation
- **Adjustable 360 degree side handle** provides better control and can be removed easily
- Download the [DH38YE2 Tool Card](#)

Includes:

- Side Handle (330209)
- Dust Cover (993245)
- Depth Stopper (971786)
- Case (331965)

Specifications

Shank	Spline
Chuck Size	1-1/2"
No-Load Speed	620 RPM

Full-Load Impact	2,800 BPM
Impact Energy	5.9 ft/lbs
Amps	8.4
Watts	950
Capacity: Solid Bit	1-1/2"
Capacity: Core Bit	4-1/8"
No-Load Vibration Level	4.8 m/s ²
Full-Load Vibration	18.8 m/s ²
No-Load Noise Level	84.5 dB
Full-Load Noise Level	95.2 dB
Modes	Hammer Only/ Hammer-Drill
Length	16-11/32"
Weight	14.1 lbs