

CM4SB2 4" Dry Cut Masonry Saw

Includes:

- 4" Continuous Rim Blade (728726)
- Wrench (941057)
- Box Wrench (10 mm) (940543)
- 20 mm Flange (956879)

Features:

- Click to view [Hitachi 2018 Catalog for Commercial Products](#)
- **Hefty 11.6 Amp (2,090 Watt Output) motor** produces a no-load speed of 11,500 RPM for greater cutting efficiency through the toughest materials
- **Sealed armature coil** is protected from dust and debris- ideal for dry cutting applications
- **Sealed armature coil additionally helps** to minimize vibration producing only 1.4 m/s²
- **Produces a low-noise level** of only 85dB
- **Dust resistant switch** prevents debris from entering the tool
- **Metal seated ball bearing** wards off damage to the motor caused by high temperatures and vibration, adding to its overall performance and durability
- **Short base edge-to-blade distance** for easy cuts in tight spaces
- **One touch lever** adjusts the depth of cut quickly and easily
- **Elastomer covered handle** provides a sure grip and improves comfort
- **Compact at 8-1/8" in length and lightweight at only 6.2 lbs**, this saw is easy to use all day
- **Comes with a premium 4" continuous rim diamond blade** designed for high-performance in dry-cutting
- Download the [CM4SB2 Tool Card](#)

Includes:

- 4" Continuous Rim Blade (728726)
- Wrench (941057)
- Box Wrench (10 mm) (940543)
- 20 mm Flange (956879)

Specifications

Amps	11.6
Power Input	1,320 W
RPM (No-Load)	11,500 /min
Max Wheel Diameter	4-3/8"
Arbor	20mm & 7/8

Model: 20mm & 1/8"

Max Cutting Depth: 1-3/8"

Metal Bearing Holder: Yes

Soft Grip Handle: Yes

Sealed Armature Coil: Yes

Depth Setting: Lever

Base edge-to-base distance: 1-7/64"

Case: No

Bevel: No

Water Feed: No

Overall Length: 8-1/8"

Weight: 6.2 lbs

