

# C8FSE 8-1/2" Sliding Compound Miter Saw

## Includes:

- 8-1/2" 24T TCT Saw Blade (998840)
- Dust Bag (322955)
- Vice Assembly (329860)
- 10mm Box Wrench (940543)
- Sub Fence (329464)

## Features:

- **Positive miter stops** for quick adjustments to 15, 22.5, 31.6, and 45 degrees to the left and right.
- **Precise compound cuts** with 48 degree bevel angle left and 5 degree bevel angle right
- **Only 31lbs** for lightweight portability
- **Powered by a 9.5 Amp motor** with a no-load speed of 5,500 RPM to smoothly handle the toughest cutting applications
- **Sturdy construction** stands up to jobsite travel and tough high-volume tasks while retaining accurate measurements
- **Easy-to-read measurements and quick settings** on miter and bevel scales
- **Linear ball bearing slide system** for superior accuracy and ease of use
- **Vertical handle** with soft, vibration reducing elastomer grip
- **Electronic speed control** for consistent RPM while cutting for maximum control
- **Adjustable pivot fence** broadly supports work piece, such as crown molding lying flat, for improved stability while cutting
- **Splinter guard** reduces tear out and increases user safety
- **Externally replaceable carbon brushes** for prolonged life of the tool
- **Dust collector attachment** minimizes airborne particles
- Download the [C8FSE Tool Card](#)

## Includes:

- 8-1/2" 24T TCT Saw Blade (998840)
- Dust Bag (322955)
- Vice Assembly (329860)
- 10mm Box Wrench (940543)
- Sub Fence (329464)

## Specifications

Amps	9.2
No-Load Speed	5,500 RPM
Blade Diameter	8-1/2"
Arbor Size	5/8"
Bevel Angle Range	Right 0-5 Degrees, Left 0-48 Degrees
Miter Angle Range	Right 0-57 Degrees, Left 0-45 Degrees

Miter Detent Stops (R & L)	15, 22.5, 31.6, 45 Degrees
Cross Cut Capacity (90 Degree)	2-9/16" x 12"
Splinter Guard	Yes
Soft Grip Handle	Yes
Sub Fence	Yes
Width	21-27/32"
Length	31-3/32"
Height	19-3/32"
Weight	31 lbs

---