

DH28PFY 1-1/8" 3-Mode D-Handle SDS Plus Rotary Hammer w/ UVP User Vibration Protection

Includes:

- Depth Gauge (310331)
- Side Handle (325273)
- Plastic Case (370155)

Features:

- **Compatible with [Hitachi 308776 Dust Collection Attachment](#)**
- **Click to view [Hitachi 2018 Catalog for Commercial Products](#)**
- **Click to view the [Dust Collection Attachment 115451](#)**
- **Featuring User Vibration Protection (UVP) technology** to reduce the vibration transfer to the user, potentially lowering the risk of a vibration related injury due to prolonged exposure
- **Increased durability** achieved by incorporating an optimized hammering mechanism similar to Hitachi's larger hammer line
- **Faster drilling speed** achieved by combining the powerful motor and optimized hammering mechanism
- **8 Amp motor that produces 2.5 ft/lbs of impact energy** for powerful hammering with fast drilling
- **0-4,300 full-load impact rate** delivers forcible hammering
- **Electronic variable speed control** gives the tool a no-load RPM of between 0-1,110 and 0-780 in reverse
- **3-modes of operation**; drilling only, hammering only and hammer drilling for flexibility within a range of applications
- **Larger side mounted mode selector dial** makes transitioning between modes simple and efficient, even when wearing gloves
- **Angle adjustment position** available on mode selector dial to change the chisel bit to different angles
- **One-push bit mounting** makes changing out bits quick and easy
- **"D" shaped rear handle** for better control in overhead applications
- **Double-molded 360 degree side handle** for comfortable operation and better control
- **Depth gauge** for consistent drilling depths
- **Push-button reversing switch** to easily back out bits
- **Lock-on speed button** for continuous operation, reduces user fatigue
- **6.9 lbs**: lightweight and compact for better maneuverability
- **Elastomer coated D-handle** helps to absorb vibration and provide a secure grip
- Download the [DH28PFY Tool Card](#)

Includes:

- Depth Gauge (310331)
- Side Handle (325273)
- Plastic Case (370155)

Specifications

Shank Size 1-1/8"

Shank Type SDS Plus

Amps	8
Modes	3
No-Load Speed	0-1,110 RPM
Impact Energy	2.5 ft/lbs
Impacts/min	0-4,300 IPM (full load)
Voltage	AC/ 120v
Capacity-Concrete:1-1/8"	
Capacity-Core Bit: 2"	
Tool Weight	6.9 lbs
Warranty	1-Year

